

OVERALL

www.overallsupply.com



INDUSTRIAL STRENGTH *PRODUCTS*
***FOR* INDUSTRIAL SOLUTIONS**

823 EAST GATE DR. • UNIT #2 • MT. LAUREL, NJ 08054
(856) 727-0880 • (800) 345-4997 • FAX: (856) 722-9630



RTV Black Silicone
RTV Blue Silicone
RTV Red Silicone (High Temp)

Seals, Bonds, Insulates • Flexible • Easy to Use • Waterproof • Weatherproof
Eliminates: Squeeze Tubes and Cartridge Guns • 100% Low Volatile R.T.V. Silicone
Safe to use on oxygen sensor equipped vehicles • Makes any size or shape gasket instantly
Flexible from -60°F to +500°F (RTV Red Silicone: temperatures from -60°F to +600°F)
Eliminates need to stock conventional gaskets and seals
Reduces down time - gets equipment back in operation fast

The Black, Blue, and Red R.T.V. Sealant Adhesives can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, these products replace a wide range of cork, paper, asbestos, felt and metal gaskets. The Black, Blue, and Red R.T.V. Sealant Adhesives have excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 600°F (RTV Red Silicone: up to 650°F) and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.

RTV Clear Silicone
Super White RTV Silicone



Seals, Bonds, Insulates • Flexible • Easy to Use • Waterproof • Weatherproof
100% RTV Silicone - Industrial Strength • Flexible from -60°F to +500°F
Caulks tubs, sinks, showers and plumbing fixtures
Seals windows, doors, tile, marble, etc. • Bonds almost any material

This R.T.V. Silicone Caulk and Sealant is ideal for use wherever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, sills and ceiling cracks and crevices. Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines. Bonds nameplates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out. NOTE: Paint will not adhere to cured material. Not recommended for continuous immersion in water or application to porous surfaces such as masonry.